

## Specification

<b>Model Name</b>	<b>K897</b>
<b>Motherboard</b>	<b>B91</b>
CPU Supports	LGA775 CPU FSB533 / 800 Core 2 duo 1.8G (E4300), Pentium Core 2 duo 1.8G (E2160), P4 3.4G (651), Celeron D 3.2G (352), Celeron 2.0G (440)
Chipset	Intel 945GC + ICH7
System Memory	2 x 240-pin DIMM socket up to 2GB DDR2 667Mhz
Graphic Memory	Share System Memory up to 232MB
<b>LCD Panel</b>	
LCD Size	17"
Brightness (cd / m <sup>2</sup> )	up to 420nits
Maximal Resolution	1280 x 1024
Touch Screen Type	6mm thick vandal-proof ELO SAW touchscreen
Tilt Angle (Degree)	30°
Speaker	2 x 3W speakers
<b>Storage</b>	
HDD	1 x 3.5" SATA HDD
<b>Expansion</b>	
Mini-PCI Socket	1
<b>I/O Port</b>	
PS2	1
USB	4
Serial / COM	4 powered COM (pin1 / pin9 with 5V / 12V power)
Parallel	1
LAN (10 / 100)	1
2nd VGA	1
Line-out	1
DC24V output	1
<b>Internal Interface</b>	
USB	USB 7,8 header
COM	5, 6 (COM 5 for touch, COM 6 for MSR)
<b>Power</b>	
Power Supply	250W ATX
EMC & Safety	FCC / CE Class A, LVD
Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
Storage Temperature	-20°C ~ 55°C (-4°F ~ 140°F)
Operating Humidity	20% - 80% RH non condensing
Storage Humidity	20% - 85% RH non condensing
<b>OS Support</b>	Windows XP, WEPOS, XP Embedded, XP professional for Embedded, WIN 2000 professional Embedded, Linux

Product specifications subject to change without prior notice.

©2008 Flytech Technology Co., Ltd. Registered trademarks and trademarks are property of their respective owners. The specification is subject to change without prior notice. Flytech endeavors to ensure that the information in this document is correct and fairly stated but does not accept liability for any error or omissions. The development of Flytech products and services is continuous, and published information may not be up to date. It is important to check the current position with Flytech.

## FLYTECH TECHNOLOGY CO., LTD.

### Taiwan - Taipei

No.168, Sing-ai Rd., Neihu District, Taipei City 114, Taiwan  
Tel: 886-2-8791-4988 Fax: 886-2-8791-4966  
Web: www.flytech.com  
E-mail: sales@flytech.com.tw

### U.S.A. - California

47825 Warm Springs Boulevard, Fremont, CA 94539, USA  
Tel: 1-510-257-5180  
Fax: 1-510-257-5181  
E-mail: sales@flytech.com

### China - Shanghai

3F Building 39, No.333 Qin Jiang Rd., Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555  
Fax: 86-21-5426-1001  
Website: www.flytech.com.cn  
E-mail: sales@flytech.com.cn

### China - Hong Kong

Room 01, 6/F, Block A, Tonic Industrial Centre, 26 Kai Cheung Rd.,  
Kowloon Bay, Kowloon, Hong Kong  
Tel: 852-3525-5800  
Fax: 852-2751-7447  
Website: www.flytech.com.hk  
E-mail: sales@flytech.com.hk

# FLYTECH K897

## Multifunction Freestanding Kiosk



*Elegant*

Versatility

*Robust*

Functionality

*ADA Compliant*

Serviceability

## Descriptions

Under an undoubted elegant and stylish appearance, K897 is much more than just skin deep. A user friendly ADA compliant kiosk equipped with 17-inch hi-brightness LCD monitor, vandal-proof touchscreen, 2mm thick metal enclosure with industrial powder coat finish plus a pair of constructive aluminum side rods, K897 is announcing its robustness, durability and perfect fit for most unattended indoor public access areas.

Adopting Intel® 945GC chipset, Core 2 Duo CPU and up to 2GB DDRII memory, K897 high performance PC engine could fulfill all kinds of kiosk application / software requirements.

A full range of peripheral options are all modular integrated into K897 for quick and easy maintenance. K897 is the ultimate of versatility, functionality and serviceability.

## Applications



## Features



**17-inch LCD main display**  
6mm vandal-proof SAW touchscreen  
Stereo Speakers

**Upgradeable front access peripheral cabinet with sliding rails**

**Front access door of bottom compartment for storage or peripheral expansibility**

**Rear access door for computer system maintenance**

## Options

### Printer



**Thermal Printer MT-532**  
Paper width: 82.5mm  
Paper roll diameter: 80mm  
Printing speed: 150mm/s  
Auto-cutter, paper-end sensor,  
Parallel interface

### Card Reader



**Magnetic Stripe Card Reader MSR-152**  
Manual insertion, conform to ISO7811 and JIS II  
RS232 interface



**Secura Integration Module**  
32-bit processor with Xtra-C interpreter DES, triple DES and RSA encryption Backlit LCD screen - 132 x 64 resolution Rugged metal keypad RJ45 serial interface



**29-in-1 Media Card Reader**  
Slots in horizontal placement Support hot swapping, USB 2.0 hi-speed data transfer USB interface

### Bill and Coin Acceptor



**Coin Acceptor UCA1**  
8 coin channels, Anti-string  
RS232 interface



**Coin Acceptor EMP850**  
32 coin channels, stainless steel fascia USB or RS232 interface



**Bill Acceptor P77P5**  
4-way acceptance, 500-bill stacker Multi-currency database, software upgradeable, Pulse or RS232 interface

### Keyboard



**16-key encrypting keypad**  
Stainless steel fascia  
USB or RS232 interface



**Metal keyboard with trackball**  
Multi-layout available, USB interface

### Others



**Laser Barcode Scanner MiniScan**  
Compact size, high speed omnidirectional scan pattern for 1D and 2D barcode  
USB or RS232 interface



**Web camera**  
1.3 mega pixels  
SXGA resolution  
USB interface



**2nd Display**  
19" LCD  
1280 X 1064 resolution  
Stainless steel enclosure  
VGA interface