



# V-POS



## Specification

<b>CPU</b>	<ul style="list-style-type: none"> <li>■ LGA 775, Intel® Core 2 Duo / Dual Core / Pentium® D/4 /</li> <li>■ Supports 1066/800/533MHz FSB</li> </ul>
<b>Chipset</b>	<ul style="list-style-type: none"> <li>■ North Bridge Intel® 945G Express Chipset</li> <li>■ South Bridge Intel® ICH7</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>■ 2x DDR II DIMM memory slots (supports up to 4GB memory)</li> <li>■ Supports 1.8V DDR II DIMM</li> <li>■ Supports dual channel DDRII 667/533/400 DIMM</li> </ul>
<b>HDD</b>	<ul style="list-style-type: none"> <li>■ 3.5" size SATA II (Up to 500GB or above)</li> </ul>
<b>Optical Device</b>	<ul style="list-style-type: none"> <li>■ Slim CDROM / DVDROM / Combo (DVD+CDRW) / DVD±RW (Optional)</li> </ul>
<b>Display Resolution</b>	<ul style="list-style-type: none"> <li>■ 17" TFT LCD (SXGA 1280x1024)</li> </ul>
<b>Expansion Slots</b>	<ul style="list-style-type: none"> <li>■ 2x mini PCI slot (internal slot)</li> </ul>
<b>Audio</b>	<ul style="list-style-type: none"> <li>■ Built-in 2x speakers (3W)</li> <li>■ Realtek ALC655 6-channel AC'97 Rev.2.3 CODEC</li> </ul>
<b>LAN</b>	<ul style="list-style-type: none"> <li>■ Marvell 88E8053 controller supporting 10/100/1000 BASE-T Ethernet</li> </ul>
<b>USB Port</b>	<ul style="list-style-type: none"> <li>■ Max 6x USB 2.0 ports</li> </ul>
<b>VGA Port</b>	<ul style="list-style-type: none"> <li>■ Intel® 945G built in experience superior graphics with intel® GMA950</li> </ul>
<b>Multi-Media Card Reader</b>	<ul style="list-style-type: none"> <li>■ SD / MS / MMC / xD</li> </ul>
<b>Back Panel I/O Ports</b>	<ul style="list-style-type: none"> <li>■ 1x Power Connector ; 1x PS/2 Keyboard ; 1x PS/2 Mouse ;</li> <li>■ 1x RJ45 ; 2x USB 2.0 ; 1x Serial ; 1x VGA ; 1x TV Cable (RCA)</li> </ul>
<b>Side Panel I/O Ports</b>	<ul style="list-style-type: none"> <li>■ 4x USB ; 3x Audio (Line In / Line Out / MIC )</li> </ul>
<b>Wireless LAN (Optional)</b>	<ul style="list-style-type: none"> <li>■ 32bit Mini-PCI card Interface. (Optional), Support 64 and 128 bit WEP Encryption</li> <li>■ 802.11b/g</li> </ul>
<b>Touch Screen</b>	<ul style="list-style-type: none"> <li>■ Internal RS-232 for Touch Screen Control Board</li> <li>■ 17", 5 wire resistive touch screen</li> </ul>
<b>Fan Speed Control</b>	<ul style="list-style-type: none"> <li>■ The CPU fan speed can set by temperature of CPU</li> </ul>
<b>Watch Dog</b>	<ul style="list-style-type: none"> <li>■ Can be set by 500ms, 1, 2, 4 seconds period. RESET or NMI was generated when CPU did not periodically trigger the timer</li> </ul>
<b>Power Lost Recovery</b>	<ul style="list-style-type: none"> <li>■ System will auto power on when power failure</li> </ul>
<b>Power Adapter</b>	<ul style="list-style-type: none"> <li>■ Input : AC / 100~240V (50/60Hz) 2.5A      * Output : DC/20V, 7.5A 150W</li> </ul>
<b>Measurements</b>	<ul style="list-style-type: none"> <li>■ Wide : 39.2cm ; High : 36.5cm ; Thick : 8.9cm (without the stand)</li> </ul>
<b>Weight</b>	<ul style="list-style-type: none"> <li>■ 8.6Kg(with all spec) ; 6.7Kg(without stand)</li> </ul>

Specifications are subject to change without notice.

