



V-SHOP



Specification

CPU	<ul style="list-style-type: none"> ■ Intel Atom ■ Intel Celeron Mobile ■ Intel Core2Duo
BOARD	<ul style="list-style-type: none"> ■ Intel Atom ■ Intel 915GME ■ Intel 945GME
HDD	<ul style="list-style-type: none"> ■ SATA 2.5" HDD 160GB or better
Memory	<ul style="list-style-type: none"> ■ DDR2 SODIMM 1 GB or higher
VGA	<ul style="list-style-type: none"> ■ Intel internal
Display.	<ul style="list-style-type: none"> ■ 15" TFT LCD (1024×768, 5line pressure touch screen)
Internal I/O	<ul style="list-style-type: none"> ■ USB × 3(Reserved for Touch control/SCR EMV card, & Web cam) ■ PS/2 × 1(Reserved for Key board) ■ RS232 x 1(COM 4 Reserved for VFD or 2nd display) ■ RS232 x 2(COM 5 & 6 with 9pin header)
Standard I/O	<ul style="list-style-type: none"> ■ USB X 4 (Side:2, Back:2) ■ Parallel × 1 ■ RS232C X 3(+5V/12V power) ■ LAN port(Giga bit) ■ Audio port ■ PS/2 port (Mouse×1, Keyboard×1)
Option	<ul style="list-style-type: none"> ■ MSR : Track 1 & 2, 2 & 3, 1 & 2 & 3 ■ Smart card reader ■ Web camera ■ Dallas I Button reader ■ CDP : VFD Type(20 Characters, 2line) ■ 2nd display : 12" TFT LCD (800×600, Non available at ATOM) ■ DVR Card : 4channel support ■ WiFi : Mini PCI for LAN ■ VGA : Mini PCI for VGA card
Power supply	<ul style="list-style-type: none"> ■ AC 110 ~ 240V
O/S	<ul style="list-style-type: none"> ■ Windows 2000, XP, XPE, WEPOS, Linux

Specifications are subject to change without notice.