



V-SLIM



■ Specification

CPU	<ul style="list-style-type: none"> ■ Intel Atom ■ Intel Celeron Mobile
Board	<ul style="list-style-type: none"> ■ Intel Atom ■ Intel 915GME
HDD	<ul style="list-style-type: none"> ■ SATA 2.5" HDD 160 GB or better
Memory	<ul style="list-style-type: none"> ■ DDR2 SODIMM 1 GB or better
VGA	<ul style="list-style-type: none"> ■ Intel 82915GM GMCH
Internal I/O	<ul style="list-style-type: none"> ■ USB×2(Reserved for Touch controller & MSR EMV card) ■ PS/2 port×1(Reserved for Keyboard/MSR) ■ RS232 x 1(Reserved for VFD or 2nd display) ■ RS232 x 2 with pin header
Standard I/O	<ul style="list-style-type: none"> ■ Parallel x 1 ■ PS/2 x 2(Keyboard, Mouse) ■ RS232 x 3(+5/12V power) ■ USB x 4(Front 2, Rear 2) ■ Audio(Line-in/MLine-out/Mic.) ■ LAN(Gigabit)
Option	<ul style="list-style-type: none"> ■ MSR : Track 1 & 2, 2 & 3, 1 & 2 & 3 ■ Smart card reader ■ CDP : VFD Type(20 Characters, 2line) ■ 2nd display : 12"TFT LCD (800×600) ■ DVR Card : 4channel support ■ WiFi : Mini PCI for LAN ■ VGA : Mini PCI for VGA card ■ Media : Multimedia Display Board : CF type support
Power Supply	<ul style="list-style-type: none"> ■ AC 110 ~ 240V
O/S Support	<ul style="list-style-type: none"> ■ Windows 2000, XP, XPE, WEPOS, Linux

Specifications are subject to change without notice.